

Powered Digital Indicator DAZ35A

Type DAZ35A

Display for Loop Powered Systems

All standard 4 ... 20 mA pressure transmitters can be equipped with the digital indicator DAZ35A. The included labels allow to show on the display different values as mbar, psi, kN etc. .

- Easy to read 4-digit LED display
- No additional power supply required
- Range programmable
- Easy to install
- Display rotation 90°

Description

The Loop Powered Digital Indicator DAZ35A is a universal plug-in display for use with 2-wire pressure transmitters. It can also be used with other types of transmitters and converters with 4 ... 20 mA 2-wire technique.

Application

The transmitters require a 4 ... 20 mA analog output and a connector socket according to DIN 43650 standards. The plug-in display is simply mounted between the connector socket and plug of the transmitter. There are two push buttons inside the instrument to program zero and range without effort.



Technical Data

Red display 4-digit	mm	7,62
Supply	mA	4 ... 20
Display range	bar	-1999 ... 9999
Accuracy ±1 digit	%FS	0,2
Admissible current	mA	max. 60
Damping range	s	0,3 ... 20
Dimensions	mm	42x52x48
CE-conformity	EN	50081-1
and		50082-2
Standards		89/336/EWG
Decimal point		programmable
Protection type	IP	65
Voltage drop	V	≤5
Operating temperature	°C	0 ... 60
Storage temperature:	°C	-30 ... 80

Optional Accessories

- Power supply 90-264 VAC/24 VDC, 0,4 A 5779A1

The corresponding mounting instructions: 002-373m

Ordering Key

Standard Type	A	Type DAZ35 <input type="checkbox"/>
---------------	---	-------------------------------------

DAZ35A_000-200e-11.06