



The OTP-528D2 is a thermopile sensor in classic TO-46 housing. The sensor is composed of 116 elements of thermocouple in series on a floating micro-membrane having an active area of 900 x 900 μm^2 . The thermopile sensor provides nearly Johnson-noise-limited performance, which can be calculated by its ohmic series resistance. A thermistor element, with a lead connected to ground, is also provided inside the TO package for ambient temperature reference.

- TO-46 metal housing
- Thermistor temperature reference included
- Low temperature coefficient of sensitivity
- Ideally suited for ear thermometers, miniature pyrometer.

Parameter	Typ	Unit	Conditions
Sensitivity	46	V/W	500K, 5-14 μm
TC of sensitivity	0.1 \pm 0.08	%/K	Typical
Thermopile Voltage	1.5 \pm 0.5	mV	Tb:50 $^\circ\text{C}$, Ta:25 $^\circ\text{C}$ 5-14 μm
Sensitivity area in diameter	0.9x0.9	mm ²	
Resistance of thermopile	65 \pm 15	K Ω	25 $^\circ\text{C}$
TC of resistance	0.1 \pm 0.05	%/K	Typical
Time constant	20	ms	
Noise voltage	32	nV/Hz ^{1/2}	r.m.s 300K
NEP	0.7	nW/Hz ^{1/2}	500K, 5-14 μm
Normalized detectivity (D*)	1.3*10 ⁸	cm*Hz ^{1/2} /W	500K, 5-14 μm
Thermistor resistance	100 \pm 3%	K Ω	25 $^\circ\text{C}$
β value	3964 \pm 0.5%	K	25 $^\circ\text{C}$ /100 $^\circ\text{C}$
Field of view	90	$^\circ$	At 50% target signal
Cut on wavelength	5.0 \pm 0.3	μm	At 25 $^\circ\text{C}$, 50% transmittance

