

型号	温度范围	湿度范围	温度精度	湿度精度	电压范围	接口	封装	尺寸	厂家	包装	最远传输距离	价格
SHT10	-40-125℃	0-100%	±0.5℃	±4.5%RH	2.4-5.5V	S-bus	LCC	7.5x4.9x2.6mm	SENSIRION 盛思锐	2000/卷带	20 米	
SHT11	-40-125℃	0-100%	±0.4℃	±3%RH	2.4-5.5V	S-bus	LCC	7.5x4.9x2.6mm		2000/卷带		
SHT15	-40-125℃	0-100%	±0.3℃	±2% RH	2.4-5.5V	S-bus	LCC	7.5x4.9x2.6mm		400/卷带		
SHT20	-40-125℃	0-100%	±0.3℃	±3%RH	2.1-3.6V	I ² C/ S-bus	DFN	3x3x1.1mm		1500/5000 卷带	10 米	
SHT21	-40-125℃	0-100%	±0.3℃	±2%RH	2.1-3.6V	I ² C/ S-bus	DFN	3x3x1.1mm		1500/5000 卷带		
SHT25	-40-125℃	0-100%	±0.2	±1.8%RH	2.1-3.6V	I ² C/ S-bus	DFN	3x3x1.1mm		1500/5000 卷带		
SHT71	-40-125℃	0-100%	±0.4℃	±3%RH	2.4-5.5V	S-bus	DIP	19.5x5.8x3.1mm		50/卷带		
SHT75	-40-125℃	0-100%	±0.3℃	±1.8%RH	2.4-5.5V	S-bus	DIP	19.5x5.8x3.1mm		50/卷带		
SI7020-A10-IM1R	-40-125℃	0-100%	±0.3℃	±3%RH	1.9-3.6V	I ² C	DFN	3x3x0.8mm	SILICON LABS 美国芯科	2500/卷带	15 米	
SI7020-A10-GM1R	-40-85℃	0-100%	±0.3℃	±3%RH	1.9-3.6V	I ² C	DFN	3x3x0.8mm		2500/卷带	15 米	
SI7021-A10-IM1R	-40-125℃	0-100%	±0.3℃	±2%RH	1.9-3.6V	I ² C	DFN	3x3x0.8mm		2500/卷带		
SI7021-A10-GM1R	-40-85℃	0-100%	±0.3℃	±2%RH	1.9-3.6V	I ² C	DFN	3x3x0.8mm		2500/卷带		
HTS221TR	-40-120℃	0-100%	±0.5℃	±4.5%RH	1.7-3.6V	I ² C、SPI	HLGA	2x2x0.9mm	ST 意法	4000/卷带		
HTU20D	-40-125℃	0-100%	±0.3℃	±3%RH	1.5-3.6V	I ² C	DFN	3x3x0.9mm	MEAS 精量	1500/卷带		
HTU21D	-40-125℃	0-100%	±0.3℃	±2%RH	1.5-3.6V	I ² C	DFN	3x3x0.9mm		1500/卷带		
HDC1000YPA	-20-85℃	0-100%	±0.2℃	±3%RH	3-5V	I ² C	DSBGA	2.1x1.65mm	TI 德州仪器	250/3000 卷带		
HDC1008YPA	-40-125℃	0-100%	±0.2℃	±4%RH	3-5V	I ² C	DSBGA	2x1.6mm		250/3000 卷带		
QM1H0P0073	-20-85℃	0-100%	±0.3℃	±2%RH	1.8-5.5V	I ² C	QFN	3x3x0.8mm	SHARP 夏普			