

ME600 – Multi-axis digital readout, without auxiliary display

- Up to 3 axes displayed, up to 4 input axes.
- 7-digit display h = 17 mm.
- Variable resolution, selectable up to 0.5 μm .
- Tactile watertight front keyboard, protected against electrostatic discharges.
- Easy and immediate use thanks to dedicated keys and coded functions.
- Acoustic and visual signals guiding the operator.
- Excellent operating reliability.
- High versatility: applicable on different types of machine-tools, since it is keyboard-programmed.
- Options available, such as relay outputs and serial output.

ME622 – ME623

With 2 displays

Display	7 high-efficiency digits h = 17 mm
Input axes	2 - 3
Applicable to	lathe - milling machine - boring machine - etc.
Signal input per axis	2 square waves out of phase $90^\circ \pm 5^\circ$ and zero ref. 5 Vdc or 12 Vdc
Power supply	230 Vac $\pm 10\%$ - 50/60 Hz 30 mA 110 Vac $\pm 10\%$ - 60 Hz 60 mA 24 Vac $\pm 10\%$ - 50/60 Hz 300 mA
Memory	permanent for configuration and special functions
Available resolutions	200 - 100 - 50 - 20 - 10 - 5 - 2 - 1 - 0.5 μm $1^\circ - 0.5^\circ - 0.2^\circ - 0.1^\circ - 0.05^\circ - 0.02^\circ - 0.01^\circ$ 0.005 $^\circ - 0.002^\circ - 0.001^\circ$
Protection class	keyboard IP 67 rear panel IP 42
Options	relay outputs (1/2/3) serial output RS-232 standard autonomy battery 1.5 h double autonomy battery 3 h



2-axis version

ME633 – ME634

With 3 displays

Display	7 high-efficiency digits h = 17 mm
Input axes	3 - 4
Applicable to	lathe - milling machine - boring machine - etc.
Signal input per axis	2 square waves out of phase $90^\circ \pm 5^\circ$ and zero ref. 5 Vdc or 12 Vdc
Power supply	230 Vac $\pm 10\%$ - 50/60 Hz 30 mA 110 Vac $\pm 10\%$ - 60 Hz 60 mA 24 Vac $\pm 10\%$ - 50/60 Hz 300 mA
Memory	permanent for configuration and special functions
Available resolutions	200 - 100 - 50 - 20 - 10 - 5 - 2 - 1 - 0.5 μm $1^\circ - 0.5^\circ - 0.2^\circ - 0.1^\circ - 0.05^\circ - 0.02^\circ - 0.01^\circ$ 0.005 $^\circ - 0.002^\circ - 0.001^\circ$
Protection class	keyboard IP 67 rear panel IP 42
Options	relay outputs (1/2/3) serial output RS-232 standard autonomy battery 1.5 h double autonomy battery 3 h



3-axis version

MAIN FUNCTIONS ME600

- SELF-TEST/ MANUAL TEST
- MIDPOINT CALCULATION
- MEMORY CLEARING
- CONSTANT PITCH
- INVERSION OF COUNTING DIRECTION
- RESETTING/PRESETTING OF A DIMENSION
- MM/INCH CONVERSION MODE
- ANGULAR READING
- SEXAGESIMAL DEGREES READING
- ABS/INC COUNTING
- SCALE ZERO REF.
- 100 OFFSET TOOL SELECTION
- VARIABLE RESOLUTION
- RADIUS/DIAMETER CONVERSION
- SCALE FACTOR
- LINEAR CORRECTION
- AXIS COUPLING