

PENKO Engineering B.V.



960 Indicator specifications

The Experts In Weighing & Dosing

Your partner for fully engineered factory solutions



PENKO

an ETC Company

PENKO Engineering B.V.

960 Indicator Specifications

A simple, precise and stable low cost weight indicator

| Type | Standard |
|--------------------------|-------------------------|
| Wiring | With sense |
| Type of sense | Passive |
| Power supply | 10,8 - 14,4 Vdc; 1 Watt |
| | 21,6 - 28,8 Vdc; 1 Watt |
| Load cell power supply | 5 Vdc |
| Sensitivity | 0,8 μ V/d |
| Sensitivity range | -0,05 mV/V to +3 mV/V |
| Measuring range | -0,25 mV to +15 mV |
| A/D Conversion speed | 15/s |
| Max. load cell impedance | 1100 Ω |
| Min. Load cell impedance | 43,75 Ω |
| Max. no. of load cells | 350 Ω 8 |
| | 1000 Ω 16 |
| Max. number of d | 10.000 |
| Display resolution | 100.000 |
| Display steps | 1,2,5,10,20,50,100,200 |
| Display size | 14mm; 7 segments LED |
| Inputs, 24 V (not free) | 6 |
| Outputs, 24 V | 2, open drain |
| Printer on/off output | Yes |
| Communication | RS232 Yes |
| Auto power off | 10 sec |
| Protection class | IP65 |
| Height | 80mm |
| Width | 160mm |
| Depth | 58mm |



PENKO Engineering B.V. | Schutterweg 35, 6718 XC Ede | The Netherlands
 Tel 0031 (0)318 525630 | Fax 0031 (0)318 529715
 info@penko.com | www.penko.com